

**Product Shipping Weight (lbs.)** 0.0800

### **PRODUCT SPECIFICATIONS**

<b>Speaker Type</b>	Tweeter
<b>Nominal Diameter</b>	.625"
<b>Power Handling (RMS)</b>	10 watts
<b>Power Handling (max)</b>	20 watts
<b>Impedance</b>	6 ohms
<b>Sensitivity</b>	89 dB @ 1W/1m
<b>Frequency Response</b>	3,500 - 27,000 Hz
<b>Voice Coil Diameter</b>	16 mm

### **THIELE-SMALL PARAMETERS**

<b>DC Resistance (Re)</b>	5.0 ohms
<b>Voice Coil Inductance (Le)</b>	0.05 mH
<b>Resonant Frequency (Fs)</b>	2,283.0 Hz
<b>Mechanical Q (Qms)</b>	2.42
<b>Electromagnetic Q (Qes)</b>	3.10
<b>Total Q (Qts)</b>	1.36
<b>Surface Area Of Cone (Sd)</b>	2.0 cm <sup>2</sup>

### **MATERIALS OF CONSTRUCTION**

<b>Cone / Diaphragm Material</b>	Textile Soft Dome
<b>Voice Coil Material</b>	Copper
<b>Voice Coil Former</b>	Aluminum
<b>Dual Voice Coil</b>	No
<b>Magnet Material</b>	Neodymium
<b>Shielded</b>	No

### **MOUNTING INFORMATION**

<b>Overall Outside Diameter</b>	32.5 mm
<b>Overall Depth</b>	14.5 mm
<b>Baffle Cutout Diameter</b>	25 mm