

**Product Shipping Weight (lbs.)** 1.8000

### **PRODUCT SPECIFICATIONS**

<b>Speaker Type</b>	Tweeter
<b>Nominal Diameter</b>	1.125"
<b>Power Handling (RMS)</b>	100 watts
<b>Power Handling (max)</b>	200 watts
<b>Impedance</b>	4 ohms
<b>Sensitivity</b>	88 dB @ 1W/1m
<b>Frequency Response</b>	1,300 - 20,000 Hz
<b>Voice Coil Diameter</b>	29 mm

### **THIELE-SMALL PARAMETERS**

<b>DC Resistance (Re)</b>	3.0 ohms
<b>Voice Coil Inductance (Le)</b>	0.04 mH
<b>Resonant Frequency (Fs)</b>	592.2 Hz
<b>Mechanical Q (Qms)</b>	1.50
<b>Electromagnetic Q (Qes)</b>	0.94
<b>Total Q (Qts)</b>	0.58
<b>Surface Area Of Cone (Sd)</b>	6.6 cm <sup>2</sup>

### **MATERIALS OF CONSTRUCTION**

<b>Cone / Diaphragm Material</b>	Metal Dome
<b>Voice Coil Material</b>	Copper
<b>Voice Coil Former</b>	Aluminum
<b>Dual Voice Coil</b>	No
<b>Magnet Material</b>	Ferrite
<b>Shielded</b>	No

### **MOUNTING INFORMATION**

<b>Overall Outside Diameter</b>	104.8 mm
<b>Overall Depth</b>	45.9 mm
<b>Baffle Cutout Diameter</b>	83.4 mm
<b># Mounting Holes</b>	4