

Product Shipping Weight (lbs.)	1.4000
---------------------------------------	--------

PRODUCT SPECIFICATIONS

Speaker Type	Full Range
Nominal Diameter	4"
Power Handling (RMS)	30 watts
Power Handling (max)	60 watts
Impedance	8 ohms
Sensitivity	85.6 dB @ 1W/1m
Frequency Response	87 - 20,000 Hz
Voice Coil Diameter	25.9 mm

THIELE-SMALL PARAMETERS

DC Resistance (Re)	6.05 ohms
Voice Coil Inductance (Le)	0.48 mH
Resonant Frequency (Fs)	87.5 Hz
Mechanical Q (Qms)	2.52
Electromagnetic Q (Qes)	0.71
Total Q (Qts)	0.55
Diaphragm Mass Inc. Airload (Mms)	2.60 g
Mechanical Compliance of Suspension (Cms)	1.27 mm/N
Surface Area Of Cone (Sd)	37.4 cm ²
Volume of Displacement (Vd)	13.1 cm ³
BL Product (BL)	3.50 Tm
Compliance Equivalent Volume (Vas)	2.5 liters
Maximum Linear Excursion (Xmax)	3.5 mm

MATERIALS OF CONSTRUCTION

Cone / Diaphragm Material	Black Anodized Aluminum Cone
Surround Material	Rubber
Voice Coil Material	Copper
Voice Coil Former	Aluminum
Dual Voice Coil	No
Basket/Frame Material	Cast Aluminum
Magnet Material	Ferrite
Shielded	No

MOUNTING INFORMATION

Overall Outside Diameter	98 mm
Overall Depth	51 mm
Baffle Cutout Diameter	77.2 mm
# Mounting Holes	6