

| | |
|---------------------------------------|---------|
| Product Shipping Weight (lbs.) | 42.4000 |
|---------------------------------------|---------|

PRODUCT SPECIFICATIONS

| | |
|-----------------------------|-----------------|
| Speaker Type | Subwoofer |
| Nominal Diameter | 18" |
| Power Handling (RMS) | 900 watts |
| Power Handling (max) | 1800 watts |
| Impedance | 4 ohms |
| Sensitivity | 89.2 dB @ 1W/1m |
| Frequency Response | 20 - 500 Hz |
| Voice Coil Diameter | 76.2 mm |

THIELE-SMALL PARAMETERS

| | |
|--|-------------------------|
| DC Resistance (Re) | 3.41 ohms |
| Voice Coil Inductance (Le) | 2.10 mH |
| Resonant Frequency (Fs) | 19.6 Hz |
| Mechanical Q (Qms) | 3.9 |
| Electromagnetic Q (Qes) | 0.43 |
| Total Q (Qts) | 0.39 |
| Diaphragm Mass Inc. Airload (Mms) | 425.9 g |
| Mechanical Compliance of Suspension (Cms) | .15 mm/N |
| Surface Area Of Cone (Sd) | 1164.0 cm ² |
| Volume of Displacement (Vd) | 1,484.1 cm ³ |
| BL Product (BL) | 20.4 Tm |
| Compliance Equivalent Volume (Vas) | 298.0 liters |
| Maximum Linear Excursion (Xmax) | 12.75 mm |

MATERIALS OF CONSTRUCTION

| | |
|----------------------------------|------------------------------|
| Cone / Diaphragm Material | Black Anodized Aluminum Cone |
| Surround Material | Rubber |
| Voice Coil Material | Copper |
| Voice Coil Former | Black Anodized Aluminum |
| Dual Voice Coil | No |
| Basket/Frame Material | Cast Aluminum |
| Magnet Material | Ferrite |
| Shielded | No |

MOUNTING INFORMATION

| | |
|---------------------------------|----------|
| Overall Outside Diameter | 461.5 mm |
| Overall Depth | 227 mm |
| Baffle Cutout Diameter | 424 mm |
| # Mounting Holes | 8 |