



15HP1020

15" - 700 W - 98 dB

NOMINAL SPECIFICATIONS

Nominal Diameter	380 mm (15 in)
Overall Diameter	393 mm (15.47 in)
Bolt Circle Diameter	374 mm (14.72 in)
Baffle Cutout Diameter	356 mm (14.02 in)
Depth	181.3 mm (7.14 in)
Flange and gasket Thickness	13.7 mm (0.54 in)
Net Weight	6.2 kg (13.6 lb)
Shipping Box	430 x 427 x 236 mm
(Single Carton Box)	(16.9 x 16.8 x 9.3 in)
Shipping Weight	7.2 kg (15.9 lb)

TECHNICAL PARAMETERS

Nominal Impedance	8 Ω
Minimum Impedance	6.9 Ω
AES Power Handling (1)	700 W
Maximum Power Handling (4)	1400 W
Sensitivity (1W/1m)	98 dB
Frequency Range	40 ÷ 4000 Hz
Voice Coil Diameter	100 mm (4 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	22 mm (0.87 in)
Magnetic Gap Depth	12 mm (0.47 in)
Flux Density	1.3 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	No
Cone Surround (5)	Triple Roll
NET Air Volume filled by Loudspeaker	3.9 dm ³ (0.138 ft ³)
Spider Profile	2x non-adjacent symmetrical constant height waves

THIELE & SMALL PARAMETERS

Fs	40 Hz
Re	5.5 Ω
Qes	0.28
Qms	10.2
Qts	0.27
Vas	109.6 dm ³ (3.87 ft ³)
Sd	759 cm ² (117.65 in ²)
Xmax (2)	9 mm
Xdamage (3)	16 mm
Mms	118.0 g
Bl	24.2 N/A
Le	1.2 mH
Mmd	106.2 g
Cms	0.13 mm/N
Rms	2.9 kg/s
η _o (Eta Zero)	2.45 %
EBP	143 Hz

NOTE:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
 - (2) Xmax = [(Winding Depth - magnetic gap depth)/2] + (magnetic gap depth / 3)
 - (3) Maximum excursion before permanent damage
 - (4) Maximum power is defined as 3dB greater than nominal power
 - (5) Treated Polycotton
- PATENT IT2006/000327

