



HF144

1.4" - 80 W - 109 dB

NOMINAL SPECIFICATIONS

Throat Diameter	35.6 mm (1.4 in)
Overall Diameter	123 mm (4.84 in)
90° Mounting Holes Diameter (4xM6)	102 mm (4.02 in)
Depth	63.5 mm (2.5 in)
Net Weight	2 kg (4.41 lb)
Shipping Box	185 x 170 x 122 mm
(Single Carton Box)	(7.3 x 6.7 x 4.8 in)
Shipping Weight	2.3 kg (5.1 lb)

TECHNICAL PARAMETERS

Nominal Impedance	8 Ω
Minimum Impedance	6.8 Ω
AES Power above 0.9 kHz (1)	80 W
AES Power above 0.65 kHz (1)	40 W
Maximum Power above 0.9 kHz (2)	160 W
Maximum Power above 0.65 kHz (2)	80 W
Minimum Crossover Frequency (3)	0.9 kHz
Sensitivity (1W/1m) (4)	109 dB
Frequency Range	0.7 ÷ 18 kHz
Voice Coil Diameter	65 mm (2.56 in)
Winding Material	Al
Former Material	Kapton
Diaphragm Material	Ketone Polymer
Diaphragm Shape	Dome
Winding Depth	3 mm (0.12 in)
Magnetic Gap Depth	4.2 mm (0.17 in)
Flux Density	1.7 T
Magnet	Neodymium Slug Crown
Re	5.5 Ω
Phase Plug Design	Annular
NET Air Volume filled by HF Driver	0.55 dm ³ (0.019 ft ³)

NOTE: Driver Mounted on FaitalPRO LTH142 horn

(1) 2 Hours Test According to AES 2-1984 Rev. 2003

(2) Maximum power is defined as 3 dB greater than nominal power.

(3) 12 dB/oct or higher slope high-pass filter.

(4) Averaged within the frequency range.

