



## 8" Ceramic Woofer

<b>Program Power</b>	<b>260 W</b>
<b>Rated impedance</b>	<b>8 Ohm</b>
<b>Nominal diameter</b>	<b>8"- 200 mm</b>
<b>Sensitivity (2,83V/1m)</b>	<b>90 dB</b>
<b>Voice coil diameter</b>	<b>1,5 in - 38 mm</b>
<b>Frequency Range</b>	<b>30-5000 Hz</b>

### SPECIFICATIONS

Nominal Diameter	8"- 200 mm	
Rated Impedance	8 Ohm	
Nominal Power Handling <sup>1</sup>	130 W	
Program Power <sup>2</sup>	260 W	
Sensitivity <sup>3</sup>	90 dB	
Frequency Range <sup>4</sup>	30-5000 Hz	
Minimum Impedance	-	
Gasket Material	Aluminum	
Magnet Material	Ferrite	
Cone Material	Doped cellulose fiber	
Cone Shape	Exponential	
Surround	Rubber	
Suspension	Nomex Fabric	
Voice Coil Diameter	1,5 in - 38 mm	
Voice Coil Winding Material	Copper	
Voice Coil Length	16 mm - 6,3 in	
Voice Coil Former Material	Kapton	
Connection type	-	
Ferrofluid	No	
Magnetic Gap Height	8 mm - 0,31 in	
Max. Peak to Peak Excursion Xvar	-	
Efficiency Bandwidth Product EBP	78	
Recommended Loading	Vented Box	
Volume / Tuning frequency	45 Lt (dm <sup>3</sup> ) - 1,589 cuft / 33 Hz	
Maximum recommended frequency	-	
Version - Part Code	<b>8 Ohm</b>	<b>HWB200</b>
	4 Ohm	HWB200-4

### T/S PARAMETERS

8 Ohm

Resonance frequency	Fs	32 Hz
DC Resistance	Re	5,5 Ohm
Mechanical Q Factor	Qms	7,5
Electrical Q Factor	Qes	0,41
Total Q Factor	Qts	0,39
BI Factor	BI	8,9 Tm
Effective Moving Mass	Mms	29,5 g
Equivalent Cas air loaded	Vas	59 lt (dm <sup>3</sup> ) - 2,084 cuft
Suspension Compliance	Cms	-
Effective Piston Diameter	D	169 mm - 6,654 in
Effective piston area	Sd	223 cm <sup>2</sup> - 34,57 sq.in
Max. Linear Excursion <sup>5</sup>	Xmax	7 mm - 0,28 in
Voice Coil Inductance @ 1kHz	Le	0,42 mH
Half-space Efficiency	η0	0,47 %

### NOTES

<sup>1</sup> Nominal power is determined according to AES2-1984 (r2003) standard.

<sup>2</sup> Program Power is defined as 3 dB greater than the Nominal rating.

<sup>3</sup> Sensitivity represents the averaged value of acoustic output as measured on the forward central axis of cone, at distance 1m, when connected to 2,83V sine wave test signal.


<sup>4</sup> Frequency range is given as the band of frequencies delineated by the lower and upper limits where the output level drops by 10 dB below the rated sensitivity in half space environment.

<sup>5</sup> Linear Math. Xmax is calculated as (Hvc-Hg)/2 + Hg/4 where Hvc is the coil depth and Hg is the gapdepth.



<sup>6</sup> Frequency response curve in the range above 150 Hz is measured on infinite baffle conditions and simulated as per recommended loading in the range below 150 Hz.

<sup>7</sup> Impedance curve is measured in free air conditions at small signals.

### FREQUENCY RESPONSE CURVE <sup>6</sup>



### FREE AIR IMPEDANCE CURVE <sup>7</sup>



### MOUNTING AND SHIPPING INFORMATION

Overall Diameter	224 mm - 8,82 in
Baffle Cutout Diameter	184 mm - 7,24 in
Flange and Gasket Thickness	7,5 mm - 0,3 in
Total Depth	94,5 mm - 3,72 in
Bolt Circle Diameter	210 mm - 8,27 in
Bolt Holes Quantity and Diameter	8 / 5,5 mm - 0,22 in
Net Weight	- - -
Shipping Units	4 Pcs