



15HP1060

15" - 1000 W - 97 dB

NOMINAL SPECIFICATIONS

Nominal Diameter	380 mm (15 in)
Overall Diameter	393 mm (15.47 in)
Bolt Circle Diameter	374 mm (14.72 in)
Baffle Cutout Diameter	354 mm (13.94 in)
Depth	194.3 mm (7.65 in)
Flange and gasket Thickness	13.7 mm (0.54 in)
Net Weight	7.1 kg (15.7 lb)
Shipping Box	430 x 427 x 236 mm
(Single Carton Box)	(16.9 x 16.8 x 9.3 in)
Shipping Weight	8.4 kg (18.5 lb)

TECHNICAL PARAMETERS

Nominal Impedance	8 Ω
Minimum Impedance	6.4 Ω
AES Power Handling (1)	1000 W
Maximum Power Handling (4)	2000 W
Sensitivity (1W/1m)	97 dB
Frequency Range	40 ÷ 2000 Hz
Voice Coil Diameter	100 mm (4 in)
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	28.9 mm (1.14 in)
Magnetic Gap Depth	12 mm (0.47 in)
Flux Density	1.22 T
Magnet	Neodymium Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround (5)	Triple Roll
NET Air Volume filled by Loudspeaker	4.1 dm ³ (0.145 ft ³)
Spider Profile	2x non-adjacent symmetrical variable height waves

THIELE & SMALL PARAMETERS

Fs	40 Hz
Re	5 Ω
Qes	0.32
Qms	11.4
Qts	0.31
Vas	87.5 dm ³ (3.09 ft ³)
Sd	780 cm ² (120.90 in ²)
Xmax (2)	12.45 mm
Xdamage (3)	21 mm
Mms	156.3 g
Bl	24.8 N/A
Le	1.32 mH
Mmd	143.9 g
Cms	0.10 mm/N
Rms	3.44 kg/s
η _o (Eta Zero)	1.70 %
EBP	125 Hz

NOTE:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) $X_{max} = [(Winding\ Depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth / 3)$
- (3) Maximum excursion before permanent damage
- (4) Maximum power is defined as 3dB greater than nominal power
- (5) Treated Polycotton

