

Product Shipping Weight (lbs.)	0.7000
---------------------------------------	--------

PRODUCT SPECIFICATIONS

Speaker Type	Full Range
Nominal Diameter	3.50"
Power Handling (RMS)	30 watts
Power Handling (max)	60 watts
Impedance	8 ohms
Sensitivity	81.8 dB @ 1W/1m
Frequency Response	70 - 17,000 Hz
Voice Coil Diameter	25 mm

THIELE-SMALL PARAMETERS

DC Resistance (Re)	7.4 ohms
Voice Coil Inductance (Le)	1.42 mH
Resonant Frequency (Fs)	69.6 Hz
Mechanical Q (Qms)	3.08
Electromagnetic Q (Qes)	0.46
Total Q (Qts)	0.4
Diaphragm Mass Inc. Airload (Mms)	5.2 g
Mechanical Compliance of Suspension (Cms)	1.00 mm/N
Surface Area Of Cone (Sd)	30.4 cm ²
Volume of Displacement (Vd)	12.2 cm ³
BL Product (BL)	6.0 Tm
Compliance Equivalent Volume (Vas)	1.31 liters
Maximum Linear Excursion (Xmax)	5.1 mm

MATERIALS OF CONSTRUCTION

Cone / Diaphragm Material	Aluminum Cone
Surround Material	Rubber
Voice Coil Material	Aluminum
Voice Coil Former	Polyimide
Dual Voice Coil	No
Basket/Frame Material	Stamped Steel
Magnet Material	Ferrite
Shielded	No

MOUNTING INFORMATION

Overall Outside Diameter	103.5 mm
Overall Depth	56.4 mm
Baffle Cutout Diameter	85 mm
# Mounting Holes	4